FUGAMAGICA® ZEROSEI **MATERIA**



FUGAMAGICA® ZEROSEI **MATERIA** COLOR EVOLUTION

MATERIA SEALANTS

ADESITAL



COLOR EVOLUTION

MATERIA SEALANTS

ADESITAL

ADEPOXY

ADESIL MATERIA









MATERIA

SEALANTS

Matter meets surface and merges with it, resulting in the new ADESITAL sealants, which interpret the nuances of stone, wood, cement and the world of colours.

FUGAMAGICA ZEROSEI **MATERIA** 40 COLORS

Water-repellent cement-based decorating sealantfor grouting 0-6 mm fade nor change upon exposure to the joints between ceramic tiles.

- 40 colours in the 4 collections: LEGNO, COLORE. CEMENTO. PIETRA.
- Classified CG2WA according to the norm EN13888: the highest mechanical and performance features.
- Classified EC1 Plus. With very low emission of settings. Volatile Organic Compounds (VOC) to safeguard indoor health.
- Water-repellent. They contrast the water passage and keep substrates dry.
- They contrast rising efflorescence and decrease the risk of unpleasant floating.

- Resistant to UV rays. Colours do not
- Resistant to alkali and detergents keeping their aspect unchanged in time.
- Resistant to the formation of mildew.
- They contrast the formation and development of mildew in humid



Packages: 25 kg bag - 4x5 kg box - 4x2 kg box

ADEPOXY MATERIA

10 COLORS





Valuable two-component epoxy grout for grouting ceramic and glassy materials.

- Smooth finishing.
- Classified RG according to the norm EN 13888. High resistance to acids and
- Classified R2 according to the norm EN
- Classified EC1 Plus. With very low emission of
- Compounds (VOC) to safeguardi ndoor health.
- Easy to clean. The product can be cleaned with water alone immediately after

- Colours unaltered over time.
- Colour hues do not fade nor change upon exposure to the light.
- chemical compounds. The product has high hygienic characteristics.



Packages: 3 kg drum - comp. A 2.7 kg / comp. B 0.3 kg

ADESIL MATERIA 24 COLORS











Solvent-free silicone sealant with acetic cross-linking.

- To seal joints between ceramic and sanitaryware and between ceramic and ceramic.
- Resistant to the formation of mildew, it contrasts the formation and development of mildew in humid settings.
- Conform to EN 15651-1, EN 15651-2, EN 15651-3.
- Classified EC1 Plus. With very low emission of Volatile Organic Compounds (VOC) to safeguard indoor health.



MATERIA

SEALANTS



NEW COLORS

www.adesital.it

COLOR EVOLUTION

ADESITAL

ADESITAL